VULCANIZABLE RUBBER COMPOSITION

Patent Number:

JP11116811

Publication date:

1999-04-27

Inventor(s):

TOJO TETSUO: SHIRATA TAKASHI; HOSOYA MIKIO

Applicant(s)::

MITSUI CHEM INC

Requested Patent:

JP11116811

Application Number: JP19980227778 19980812

Priority Number(s):

IPC Classification:

C08L83/04; C08K5/14; C08L23/08; C08L47/00

EC Classification:

Equivalents:

Abstract

PROBLEM TO BE SOLVED: To obtain the subject composition having excellent strength and water resistance and improved mold staining properties and heat aging characteristics, by including a silicone rubber and a specific ethylene/&alpha -olefin/polyene amorphous copolymer.

SOLUTION: This composition (A) 2-98 wt.% of a silicone rubber and (B) 98-2 wt.% of an ethylene/&alpha olefin/polyene amorphous copolymer. The polyene is at least one kind of a terminal vinyl group-containing norbornene compound of formula I ((n) is 0-10; R<1> is H or a 1-10C alkyl; R<2> is H or a 1-5C alkyl) or formula II (R<3> is H or a 1-10C alkyl). The copolymer B is preferably an ethylene/propylene/5-methylene-2-norbornene random copolymer or an ethylene/ propylene/5-vinyl-2-norbornene random copolymer.

Data supplied from the esp@cenet database - 12